

# TILTWATCH

TM

The best way to monitor shipments that must remain upright.



Today's "just-in-time" zero defect delivery requirements demand shipping controls and monitors beyond the passive printed warnings on the sides of containers. The Tiltwatch is the best choice for goods that must remain upright to ensure intact delivery. Tiltwatch is "carrier friendly" and guarantees 100% accuracy. It's a reliable and affordable solution to monitoring and controlling the shipping attitude of heavy machinery, large computers, electronic panels, cut flowers, batteries, liquids and a host of other products.

Fifteen years of exposure through the transportation corridors of the world guarantees instant recognition.

A precision manufacturing process assures consistent quality and performance.



## Simple & foolproof

Tiltwatch is a state-of-the-art monitor that will indicate red if your container has been tilted on its side or completely upended. Normal movement or road shock will have no effect. Tiltwatch will not activate due to acute take-off angles in aircraft. It's fair to you and your carriers.

## Moistureproof

The Tiltwatch incorporates a vacuum seal that eliminates any effects of humidity or temperature changes.

## Tamperproof

The self-stick backing utilizes the most aggressive 5 mil acrylic adhesive available assuring a permanent bond on all but the roughest containers. When used with its 5"x 8" companion label, the contact area is increased (along with its visibility), which forms a more permanent bond to the host container.



### Non-resettable/ Auto-Arm feature

Tiltwatch features a simple one step application. Removing the adhesive backing automatically arms the device. Once activated the Tiltwatch cannot be reset. It is impossible to disarm the Tiltwatch once it has been applied. This is because the arming mechanism is secured facing the shipment. Other tilt indicators that arm from the front or side are subject to tampering and environmental conditions.

### The Tiltwatch program is prevention— pure and simple

A key element to the success of Tiltwatch is its simplicity. The program includes the Tiltwatch indicator and an alert sticker to be affixed to the bill of lading. It cautions the carrier and consignee that your shipment is being monitored. One alert sticker is included free with each Tiltwatch.

**NOTICE:**  
If TILTWATCH is red **ALWAYS** accept shipment. Make note on bill of lading. Inspect for damage immediately.



**MONITORED TILTWATCH™ SHIPMENT**

**CAUTION**

**CAUTION**

**IF INDICATOR IS RED**

- 1. DO NOT REFUSE SHIPMENT.**
- 2. MAKE NOTATION ON DELIVERY RECEIPT AND INSPECT FOR DAMAGE.**
- 3. IF DAMAGE IS DISCOVERED, LEAVE IN ORIGINAL CONTAINER AND PACKAGING, AND REQUEST IMMEDIATE INSPECTION FROM CARRIER WITHIN 15 DAYS OF DELIVERY. (INT'L 3 DAYS)**

MEDIA RECOVERY, INC. 1100 Preston Central Drive, Suite 750 #7 214-638-9626 Toll Free (800) 527-9497

### Tiltwatch Companion Label

The companion label, when applied with Tiltwatch, alerts shippers and provides additional instructions to your customers. With every shipment, this large, highly visible label announces that you are committed to damage reduction and also ensures that your customer knows exactly what to do if Tiltwatch is activated. Available in rolls of 200 or 500.

### About Media Recovery

When you consider what monitoring product you want associated with your brand name, what is behind our products is as important as the product itself. Media Recovery, with a twenty year track record of both financial and technical capability, has established itself as a sound and reliable source to many of the Fortune 500 companies of the world. Our customer focused field staff, strategically located around the world, assures you of rapid response under any circumstance. This, coupled with access to information via any communications medium, gives you the information you need, when you need it.

## SHOCKWATCH®

7929 Brookriver Dr. Ste. 200  
Dallas, Texas 75247  
www.shockwatch.com

(214) 630-9625  
(800) 527-9497  
fax: (214) 638-4512

### TILTWATCH SPECIFICATIONS

Activation Angle	80° +/-5% from vertical
Monitoring Range	Single Plane
Adhesive	5 mil high tack acrylic
Humidity Tolerance	0% to 100%
Temperature Tolerances	-40° C to 60° C
Composition	Rigid polystyrene housing with stainless steel indicator
Size	2.65" wide x 2.925" length - depth .190"
Installation	Pressure sensitive adhesive or holes to accommodate small screws, nails or staple for rough surfaces.
Customization	Private logos available on orders above 3500 units.
Adhesive Shelf Life	24 months